



	Pin 1	Pin2
Fan control	DC 5 V	0 V
FVOA IL control	Pin 3	Pin 4
fiber core <= 62.5um	DC 0 ~ 5.5V	0 V
fiber core 105um	DC 0~14.5V	0 V

UNLESS OTHERWISE SPECIFIED:

1.DO NOT SCALE DRAWING.
2. INTERPRET PER ASME Y14.100M.
3.DIMENSIONS ARE IN METRIC.
4.SURFACE TEXTURE SHALL BE 125
5.REMOVE BURRS AND SHARP EDGES
6.DIMENSIONS APPLY BEFORE PLATING
OR CONVERSION COATING.
7.PARENTHEICAL DATA IS FOR
REFERENCE ONLY

TOLERANCES:			
ON ALL HOLE DIAMETERS			
Under 1.0	+0.05 -0.01	25 THRU 50	+0.2 -0.1
1.0 THRU 5.0	+0.1 -0.025	>50	+0.25 -0.1
5.0 THRU 10.0	+0.15 -0.025		
10.0 THRU 25	+0.2 -0.025		
ON DECIMAL DIMENSIONS:	ON ANGULAR DIMENSIONS:		
.XXX +/-0.010	MACHINED +/-0°30'		
.XX +/-0.03	LOCATING +/-0°30'		
.X +/-0.1	FORMED +/-2°		
	CHANFERS +/-5°		

NAME	DATE
CHK'D	
APPV'D	
MFG	
Q.A	
MATERIAL:	
WEIGHT:	

DO NOT SCALE DRAWING		REVISION
TITLE: FVOA FOR MM fiber		
DWG NO.		A3
SCALE:1:2		SHEET 1 OF 1